

BADU® Eco Touch-Pro II

Solid and focused on efficiency.
The intelligent circulation pump for beginners.

Field of application

Swimming pool water circulation through a filter system.
The pump can be installed max. 3 m above or below water level.

Design

Monoblock-type pump with integrated strainer tank.
The bellow-type mechanical seal is mounted on a plastic shaft protector sleeve. Motor/pump has no contact with the pool water providing complete electrical separation.
Strainer tank capacity approx. 3 l
Strainer basket mesh size approx. 3.2 x 2.6 mm

Can be controlled using the BADU Eco Logic remote control.
Product information can be found on the BADU website:
badu.de > BADU Private > Control units > Pool regulators.

Materials used

Pump casing PP TV 20
Intermediate housing PP TV 40
Gland housing PP TV 40
Diffuser PA 6 GF 15
Impeller PA 66 GF 30
Strainer basket PP
Lid PC, transparent/PA 66 GF 30
Glue socket ABS
Mechanical seal carbon/ceramic/NBR
Screws galvanised stainless steel

Technical data at 50/60 Hz	BADU Eco Touch-Pro	II
Inlet Sa/outlet connection Da d ³⁾		63/50
Rec. inlet/outlet pipe, PVC pipe d ³⁾		63/50
Power input P ₁ /output P ₂ ¹⁾ (kW)	1~ 230 V	0.08-1.05/0.03-0.75
Rated current (A)	1~ 230 V	0.60-6.50

For more detailed information regarding the motor protection please see page 34.


Article no	Description	Voltage	Power output P ₂
219.0008.038	BADU Eco Touch-Pro II	1~ 230 V	0.75 kW

Universal opening device included in delivery. See page 29.



< Motor display with intuitive control

< With 3.5 m power cable



Performance

Dimensions

Detailed dimensions available on request or at badu.de

